



Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 11249053
Procuring Entity CARLOS HILADO MEMORIAL STATE UNIVERSITY
Title Procurement of Audio System for Fortune Towne Campus
Area of Delivery Negros Occidental

Solicitation Number:	RFQ 24-400	Status	Pending
Trade Agreement:	Implementing Rules and Regulations	Associated Components	1
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Bid Supplements	0
Classification:	Goods	Document Request List	0
Category:	Audio and Visual Equipment	Date Published	14/09/2024
Approved Budget for the Contract:	PHP 300,000.00	Last Updated / Time	13/09/2024 10:57 AM
Delivery Period:	30 Day/s	Closing Date / Time	23/09/2024 09:00 AM
Client Agency:			
Contact Person:	Rowena De la Vida Prado Administrative Assistant II Mabini Street Talisay City Negros Occidental Philippines 6115 63-34-7120005 Ext.142 63-939-9296624 bac.sec@chmsu.edu.ph		

Description

Republic of the Philippines
 CARLOS HILADO MEMORIAL STATE UNIVERSITY
 Talisay City, Negros Occidental
 Telephone: (0939) 929 6624
 bac.sec@chmsu.edu.ph

REQUEST FOR QUOTATION
 PAGE 1 OF 4
 Date: SEPTEMBER 12, 2024
 Quotation No. 24-400

Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

DR. ANDREW EUSEBIO S.TAN
 BAC Chairman

NOTE:

- ALL ENTRIES MUST BE TYPEWRITTEN
- DELIVERY PERIOD WITHIN 30 CALENDAR DAYS
- WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY
- PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS

5. G-EPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
 6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO. (Pls. Indicate brand offered)

ONE(1) LOT
 1 SPEAKER, 10" 300W 2-Way Full Range Active Loudspeaker with 6 unit Tripod Base Speaker Stand:
 System Type: 2 way Full range; LF 10" Woofer (2 Voice Coil Size);
 HF: 1" titanium Dome Tweeter; Freq. Resp. 48Hz- 20KHz;
 Power 250W; Impedance 4 omhs; Amp. Power 300W Class D;
 input Gain: Line +20 dBu/ Mic : +40dB; input Connector: lineRCA & XLR), mic (PL& XLR); output Connector: Line (XLR Loop through);
 THD: Less Than 0.1%; Signal Indicator: Power, Signal, Clip;
 Crossover Freq: 2.5KHZ; AC Input: 220V 50-60HZ; Sensitivity: 99dB;
 DIMENSIONS: L32 XW36 X H110; WEIGHT: 23 KG;
 2 MICROPHONE, 18" Cardioid Gooseneck Microphone with Flange 3 pcs
 Mount and 10 foot Side Exit Cable:
 "Frequency Response:50 to 17,000 Hz;
 Output Impedance (at 1000 " Hz):Rated at150 Ω (180 Ω actual); Open Circuit Sensitivity (at 1 kHz, ref. 1 V/Pascal*):Cardioid: -35.0 dB (17.8 mV),Supercardioid :-33.5 dB (21.1 mV),Omnidirectional: -27.5dB (42.2 mV),*1 Pascal= 94 dB SPL; Maximum SPL (1 kHz at 1% THD, 1 kΩ load): Cardioid: 124.2.0 dB,Supercardioid: 122.7 dB,Omnidirectional: 116.7 dB; Equivalent Output Noise (A-weighted):Cardioid: 28.0 dB SPL, Supercardioid: 26.5 dB SPL, Omnidirectional: 20.5 dB SPL; Signal to Noise Ratio (referenced at 94 dB SPL):Cardioid: 66.0 dB, Supercardioid: 67.5 dB,Omnidirectional: 73.5 dB; Dynamic Range at 1 kΩ Load:96.2 dB;Common Mode Rejection: 45.0 dB minimum; Preampifier Output Clipping Level (1% THD):-6.0 dBV (0.5 V); Polarity:Positive sound pressure on diaphragm produces positive, voltage on pin 2 relative to pin 3 of output connector.; Power Requirements:11 to 52 Vdc phantom, 2.0 mA; Environmental Requirements:Operating Temperature Range: -18° to 57° C (0° to 135° F),Relative Humidity: 0 to 95%;
 3 12-CHANNEL AUDIO MIXER 2 unit
 (8+2 and 12+2 channel frame sizes;Bullt-in 24 bit Lexicon digital effects processor;32 FX settings;Tap Tempo and FX setting store function 1 FX send on each channel 1 configurable auxiliary bus XLR-type and ¼" metal jack connector sockets;RCA phono stereo playback inputs and record outputs;3-band EQ with a swept mid on mono inputs;3-band EQ on stereo inputs;TRS insert sockets and inserts on all mono inputs;Ten-segment LED output metering)
 4 AUTOMATIC VOLTAGE REGULATOR (2000W) 2 unit
 Automatic Voltage Regulator 2000w ;Protects Electric Devices From Sudden Voltage Surge With Servo-Motor Control System Equipped with Overloading Protection System and Indicator Equipped with Fuse For Added Protection Multiple Universal Outlets Equipped with Fan Blower With Input and Output Meter; of reputable international brand.; ControlInput: 160v to 250v Output: 3x 220v
 5 SUBWOOFER SPEAKER, Live Sub 18.4 18 inch 1200W 4" In Out 2 unit
 Coll Subwoofer Speaker Double Magnet
 Live Sub 18.4 Subwoofer Speaker (1pc.));Speaker Type: Gapang Bass ;Size: 18inch ;Max Power: 1200watts; RMS: 800W Type: Double Magnet; VC: 4inch (in out coil); Freq response range: 80 hz-1500Hz; Sensitivity: 96db; Double spider Double treated cone
 6 MICROPHONE WIRE/CABLE, 100m 'Heavy Duty 1 roll
 Type: Stereo Microphone Wire; best in dmx cable;Color: Black; Length: 100m; Small jacket diameter, ensuring easy handling with XLR, JACK and RCA connectors
 7 AUDIO CONNECTOR, 3 Pins XLR Female Audio Jack Audio connector 13 pcs
 Contact material is brass, high conductivity, and the noise can be well shielded
 8 AUDIO CONNECTOR, 3 Pins Heavy Duty XLR Male Audio Jack 13 pcs
 Audio connector; Contact material is brass, high conductivity, and the noise can be well shielded
 9 RCA AUDIO CABLE, 5m, Jack 3.5 to 2 RCA Cable 3.5mm Jack 4 pcs to 2RCA Male Splitter Aux Cable Male RCA Round Cable
 Material: nylon braided wire + aluminum alloy; Color: dark grey
 TOTAL

*****Nothing Follows*****

TOTAL ABC = Php 300,000.00

PROCUREMENT OF AUDIO SYSTEM FOR FORTUNE TOWNE CAMPUS/ R. DELA TORRE

PR# 24-598-0708 07-08-24

INCOME 334-164-24-07 07-09-24

Line Items

Item No.	Product/Service Name	Description	Quantity	UOM	Budget (PHP)
----------	----------------------	-------------	----------	-----	--------------

1	ONE (1) LOT	Audio System	1	Lot	300,000.00
---	-------------	--------------	---	-----	------------

Created by Rowena De la Vida Prado

Date Created 13/09/2024

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.



Republic of the Philippines
CARLOS HILADO MEMORIAL STATE UNIVERSITY
 Talisay City, Negros Occidental
 Telephone: (0939) 929 6624
bac.sec@chmsu.edu.ph

REQUEST FOR QUOTATION

PAGE 1 OF 4

Date: SEPTEMBER 12, 2024
 Quotation No. 24-400

Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

DR. ANDREW EUSEBIO S.TAN
 BAC Chairman

NOTE:

- ALL ENTRIES MUST BE TYPEWRITTEN
- DELIVERY PERIOD WITHIN 30 CALENDAR DAYS
- WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY
- PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS
- G-EPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
- BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEM & DESCRIPTION (Pls. indicate brand offered)	QTY.	UNIT	UNIT PRICE	TOTAL PRICE
	ONE(1) LOT				
1	SPEAKER, 10" 300W 2-Way Full Range Active Loudspeaker with Tripod Base Speaker Stand: System Type: 2 way Full range; LF 10" Woofer (2 Voice Coil Size); HF: 1" titanium Dome Tweeter; Freq. Resp. 48Hz- 20KHz; Power 250W; Impedance 4 omhs; Amp. Power 300W Class D; inpute Gain: Line +20 dBu/ Mic : +40dB; input Connector: lineRCA & XLR), mic (PL& XLR); output Connector: Line (XLR Loop through); THD: Less Than 0.1%; Signal Indicator: Power. Signal, Clip; Crossover Freq: 2.5KHZ; AC Input: 220V 50-60HZ; Sensitivity: 99dB; DIMENSIONS: L32 XW36 X H110; WEIGHT: 23 KG;	6	unit		
2	MICROPHONE, 18" Cardioid Gooseneck Microphone with Flange Mount and 10 foot Side Exit Cable: Frequency Response:50 to 17,000 Hz;Output Impedance (at 1000 Hz):Rated at150 Ω (180 Ω actual); Open Circuit Sensitivity (at 1 kHz, ref. 1 V/Pascal*):Cardioid: -35.0 dB (17.8 mV),Supercardioid : -33.5 dB (21.1 mV),Omnidirectional: -27.5dB (42.2 mV),*1 Pascal= 94 dB SPL; Maximum SPL (1 kHz at 1% THD, 1 kΩ load): Cardioid: 124.2.0 dB,Supercardioid: 122.7 dB,Omnidirectional: 116.7 dB; Equivalent Output Noise (A-weighted):Cardioid: 28.0 dB	3	pcs		

Date _____ By _____

Released (BAC) _____
 Returned (Supplier) _____

Printed Name/Signature

Tel. No./Cellphone No.

Date



Republic of the Philippines
CARLOS HILADO MEMORIAL STATE UNIVERSITY
 Talisay City, Negros Occidental
 Telephone: (0939) 929 6624
bac.sec@chmsu.edu.ph

REQUEST FOR QUOTATION

PAGE 2 OF 4

Date: SEPTEMBER 12, 2024
 Quotation No. 24-400

Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

DR. ANDREW EUSEBIO S.TAN
 BAC Chairman

- NOTE:
- ALL ENTRIES MUST BE TYPEWRITTEN.
 - DELIVERY PERIOD WITHIN 30 CALENDAR DAYS
 - WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY
 - PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS
 - G-EPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
 - BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEM & DESCRIPTION (Pls. indicate brand offered)	QTY.	UNIT	UNIT PRICE	TOTAL PRICE
	SPL, Supercardioid: 26.5 dB SPL, Omnidirectional: 20.5 dB SPL; Signal to Noise Ratio (referenced at 94 dB SPL): Cardioid: 66.0 dB, Supercardioid: 67.5 dB, Omnidirectional: 73.5 dB; Dynamic Range at 1 kΩ Load: 96.2 dB; Common Mode Rejection: 45.0 dB minimum; Preamplifier Output Clipping Level (1% THD): -6.0 dBV (0.5 V); Polarity: Positive sound pressure on diaphragm produces positive, voltage on pin 2 relative to pin 3 of output connector.; Power Requirements: 11 to 52 Vdc phantom, 2.0 mA; Environmental Requirements: Operating Temperature Range: -18° to 57° C (0° to 135° F), Relative Humidity: 0 to 95%;				
3	12-CHANNEL AUDIO MIXER (8+2 and 12+2 channel frame sizes; Built-in 24 bit Lexicon digital effects processor; 32 FX settings; Tap Tempo and FX setting store function 1 FX send on each channel 1 configurable auxiliary bus XLR-type and ¼" metal jack connector sockets; RCA phono stereo playback inputs and record outputs; 3-band EQ with a swept mid on mono inputs; 3-band EQ on stereo inputs; TRS insert sockets and inserts on all mono inputs; Ten-segment LED output metering)	2	unit		
4	AUTOMATIC VOLTAGE REGULATOR (2000W) Automatic Voltage Regulator 2000w ; Protects Electric Devices	2	unit		

Date _____ By _____

Released (BAC) _____
 Returned (Supplier) _____

Printed Name/Signature _____

Tel. No./Cellphone No. _____

Date _____



Republic of the Philippines
CARLOS HILADO MEMORIAL STATE UNIVERSITY
 Talisay City, Negros Occidental
 Telephone: (0939) 929 6624
bac.sec@chmsu.edu.ph

REQUEST FOR QUOTATION

PAGE 3 OF 4

Date: SEPTEMBER 12, 2024

Quotation No. 24-400

Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

DR. ANDREW EUSEBIO S.TAN
 BAC Chairman

NOTE:

1. ALL ENTRIES MUST BE TYPEWRITTEN
2. DELIVERY PERIOD WITHIN 30 CALENDAR DAYS
3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY
4. PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS
5. G-EPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEM & DESCRIPTION (Pls. indicate brand offered)	QTY.	UNIT	UNIT PRICE	TOTAL PRICE
	From Sudden Voltage Surge With Servo-Motor Control System Equipped with Overloading Protection System and Indicator Equipped with Fuse For Added Protection Multiple Universal Outlets Equipped with Fan Blower With Input and Output Meter; of reputable international brand.; Control Input: 160v to 250v Output: 3x 220v				
5	SUBWOOFER SPEAKER , Live Sub 18.4 18 inch 1200W 4" In Out Coil Subwoofer Speaker Double Magnet Live Sub 18.4 Subwoofer Speaker (1pc.) ;Speaker Type: Gapang Bass ;Size: 18inch ;Max Power: 1200watts; RMS: 800W Type: Double Magnet; VC: 4inch (in out coil); Freq response range: 80 hz-1500Hz; Sensitivity: 96db; Double spider Double treated cone	2	unit		
6	MICROPHONE WIRE/CABLE , 100m 'Heavy Duty Type: Stereo Microphone Wire; best in dmx cable;Color: Black; Length: 100m; Small jacket diameter, ensuring easy handling with XLR, JACK and RCA connectors	1	roll		
7	AUDIO CONNECTOR , 3 Pins XLR Female Audio Jack Audio connector Contact material is brass, high conductivity, and the noise can be well shielded	13	pcs		

Date

By

Printed Name/Signature

Released (BAC)

Returned (Supplier)

Tel. No./Cellphone No.

Date

